

High Volume, High Speed Envelope Opening and Sorting for All Types of Mail





#### OMATION MODEL 306™

## **High-Speed Opening**

Operates at up to 40,000 envelopes per hour

# **Three Mail Tray Supports**

Permits optimized work flow & improved ergonomics

## **Operator Controlled Software Interface**

- Provides numerous job settings
- Supports multiple operators & languages with password protection
- Presents an easy-to-read backlit LCD display

## **Automatic Jam Detection**

· Reduces damage while making jam clearing easier

## **Automatic Chaff Collection**

 Provides a clean workspace, jam prevention, & reduced static buildup

# **Milling Cutter**

Offers 8 cut-depths plus "No-Cut" position

# Model 306 and 306s Optional Features

## **Batching**

Groups items into pre-selected lot sizes

# 90° Powered Conveyor

Adds capacity & larger space to manage output

## Reports Printer

 Produces a variety of statistics reports for monitoring machine performance

## **High-Speed Inkjet Printer**

- Prints a variety of custom strings, date & time, sequential numbering & ID Tag barcodes
- Prints up to 4 lines





## **OPEX World Headquarters**

305 Commerce Drive Moorestown, NJ 08057-4234 United States

Tel: +1 856.727.1100 Fax: +1 856.727.1955 **www.opex.com** 

## **OPEX United Kingdom**

Carrington Business Park Carrington Manchester, England M314YR

Tel: +44 0161.776.4033 Fax: +44 0161.776.2663

## OMATION MODEL 306s™

Coupled with enhanced sorting capabilities, the Model 306s is a perfect fit for a wide variety of applications. Envelopes can be output to two locations based on programmable criteria such as thickness, length, and height. With its ability to identify "clean mail" from "exception mail," the Model 306s helps to insure maximum productivity by opening and sorting envelopes in a single pass.

# **Sort Wizard**

• Intuitive & easy-to-use operator interface for job setup



## 306 Base Model Specifications:

Length	45" (114.3 cm)
Depth	21" (53.34 cm)
Height	58" (147.32 cm)
Weight	245 pounds
Power	115 VAC, 60HZ, 8.5A 230 VAC, 50HZ, 5.5A
BTU	3338 BTU/h (115VAC) 4317 BTU/h (230VAC)
Speed	Up to 40,000 / hour
Envelope Sizes & Types	Lengths up to 13.5" (34.29 cm)
Thickness	Up to 0.50" (1.27 cm)
Depth of Cut	From 0.01" (0.03 cm) from envelope edge up to 0.125" (0.32 cm) in depth
Feeder Hopper Capacity	Up to 400 envelopes
Stand & Waste Bin	Included

# **OPEX France**

3 avenue du Canada Parc Technopolis - ZA COURTABOEUF Bâtiment EPSILON 91940 - LES ULIS - France Tel: +33 01.60.92.40.40 **OPEX Germany** 

Max-Planck-Ring 39 65205 Wiesbaden-Delkenheim Germany

Tel: +49 6122.927.8883 Fax: +49 6122.927.8885